



## >> RP-IP509

### 4-P Broadband Router

## FEATURE

- Integrates with 4 ports Fast Ethernet switch: 10/100Mbps MDI/MDIX auto-sensing
- Provides 10/100Mbps WAN interface to connect with DSL or cable modem for broadband Internet access
- Built-in NAT function: Allows multiple PCs and devices to share one Internet connection
- Browser-based interface configuration and management: OS independent, easy-to-use for consumer installation
- Built-in firewall to protect your Intranet
- Supports PPTP, L2TP
- Easy to upgrade: using Web or Windows Application to upgrade new version of firmware

## SPECIFICATION

<b>Standards</b>	<ul style="list-style-type: none"><li>• IEEE 802.3 10Base-T Ethernet</li><li>• IEEE 802.3u 100Base-TX Fast Ethernet</li></ul>
<b>Interface</b>	<ul style="list-style-type: none"><li>• 4-P * LAN, 1-P * WAN</li></ul>
<b>Memory</b>	<ul style="list-style-type: none"><li>• Flash 512KB, DRAM 2MB</li></ul>
<b>Firmware Platform</b>	<ul style="list-style-type: none"><li>• Proprietary Kernel</li></ul>
<b>Management Method</b>	<ul style="list-style-type: none"><li>• Web-based</li></ul>
<b>WAN Type</b>	<ul style="list-style-type: none"><li>• Static IP Address</li><li>• Dynamic IP Address (DHCP Client)</li><li>• PPPoE</li><li>• PPTP</li><li>• Dial-Up Network</li></ul>
<b>Connection Scheme</b>	<ul style="list-style-type: none"><li>• Connect on Demand/Auto-Disconnect</li><li>• Manually Connect/Disconnect</li><li>• Auto Reconnect</li></ul>
<b>NAT Function</b>	<ul style="list-style-type: none"><li>• One-to-Many NAT</li><li>• One-to-One NAT</li><li>• Virtual Server</li><li>• Special Application</li><li>• DMZ Host</li></ul>
<b>Access Control</b>	<ul style="list-style-type: none"><li>• MAC-level Access Control</li><li>• Inbound/Outbound IP Filter</li><li>• Domain Access Control</li></ul>
<b>Firewall</b>	<ul style="list-style-type: none"><li>• NAT Firewall with SPI mode</li><li>• DoS Detection</li></ul>
<b>Event Logging</b>	<ul style="list-style-type: none"><li>• On-web logging</li><li>• Syslog supported</li></ul>
<b>Power Supply</b>	<ul style="list-style-type: none"><li>• External power Adapter DC9V, 1A</li></ul>
<b>Environment</b>	<ul style="list-style-type: none"><li>• Operating Temperature: -20°C~ 70°C</li><li>• Operating Humidity: 10%~90% (Non-Condensing)</li></ul>
<b>Dimension</b>	<ul style="list-style-type: none"><li>• 153 * 112 * 26 mm</li></ul>
<b>Certifications</b>	<ul style="list-style-type: none"><li>• FCC, CE</li></ul>

## Ordering Information

RP-IP509

4-P Broadband Router